



NEW PRODUCT DATA

Competition-Ready 13° Small Block Chevy Pistons
Versatile Piston Line with Ready-to-Make Availability for Popular Circle Track Builds

13° SERIES															
400 13° SERIES - ACCOMODATES ALL PRO, BRODIX, and DART 13°															
Std Bore: 4.125															
Ring package designed for: .043, .043, 3.0mm Rings															
Part #	Cubic Inches	Bore Size	Stroke	Rod Length	Block Height	Comp. Distance	Head Cubic Centimeters			Dome Volume	Gram Weight	Footnote	Oversize	Ring Set Recommended	Pro Seal Head Gasket
							40cc	45cc	50cc						
							Compression Ratio								
377972	428	4.125	4.000	6.000	9.000	1	17.6	16.2	15	-3.5	415	B, S	STD	JG7708-4125-5	GM1003-039
377973	429	4.130	4.000	6.000	9.000	1	17.6	16.2	15	-3.5	417	B, S	0.005	JG7708-4130-5	GM1003-039
377974	430	4.135	4.000	6.000	9.000	1	17.7	16.2	15	-3.5	419	B, S	0.01	JG7708-4135-5	GM1003-039
377975	431	4.140	4.000	6.000	9.000	1	17.7	16.3	15	-3.5	421	B, S	0.015	JG7708-4135-5	GM1004-039
377976	432	4.145	4.000	6.000	9.000	1	17.7	16.3	15.1	-3.5	423	B, S	0.02	JG7708-4145-5	GM1004-039
377977	433	4.150	4.000	6.000	9.000	1	17.8	16.3	15.1	-3.5	425	B, S	0.025	JG7708-4145-5	GM1004-039
377978	434	4.155	4.000	6.000	9.000	1	17.8	16.3	15.1	-3.5	427	B, S	0.03	JG7708-4155-5	GM1004-039
377979	436	4.165	4.000	6.000	9.000	1	17.9	16.4	15.2	-3.5	430	B, S	0.04	JG7708-4165-5	GM1004-039
377980	414	4.125	3.875	6.000	9.000	1.062	16.7	15.4	14.3	-4.5	TBD	B, S	STD	JG7708-4125-5	GM1003-039
377981	415	4.130	3.875	6.000	9.000	1.062	16.7	15.4	14.3	-4.5	TBD	B, S	0.005	JG7708-4130-5	GM1003-039
377982	416	4.135	3.875	6.000	9.000	1.062	16.8	15.4	14.3	-4.5	TBD	B, S	0.01	JG7708-4135-5	GM1003-039
377983	417	4.140	3.875	6.000	9.000	1.062	16.8	15.5	14.4	-4.5	TBD	B, S	0.015	JG7708-4135-5	GM1004-039
377984	418	4.145	3.875	6.000	9.000	1.062	16.8	15.5	14.4	-4.5	TBD	B, S	0.02	JG7708-4145-5	GM1004-039
377985	419	4.150	3.875	6.000	9.000	1.062	16.9	15.6	14.4	-4.5	TBD	B, S	0.025	JG7708-4145-5	GM1004-039
377986	420	4.155	3.875	6.000	9.000	1.062	16.9	15.6	14.5	-4.5	TBD	B, S	0.03	JG7708-4155-5	GM1004-039
377987	422	4.165	3.875	6.000	9.000	1.062	16.9	15.6	14.5	-4.5	TBD	B, S	0.04	JG7708-4165-5	GM1004-039
377988	406	4.125	3.800	6.000	9.000	1.1	16.4	15.1	14	-4.5	TBD	B, S	STD	JG7708-4125-5	GM1003-039
377989	407	4.130	3.800	6.000	9.000	1.1	16.5	15.2	14	-4.5	TBD	B, S	0.005	JG7708-4130-5	GM1003-039
377990	408	4.135	3.800	6.000	9.000	1.1	16.5	15.2	14.1	-4.5	TBD	B, S	0.01	JG7708-4135-5	GM1003-039
377991	409	4.140	3.800	6.000	9.000	1.1	16.5	15.2	14.1	-4.5	TBD	B, S	0.015	JG7708-4135-5	GM1004-039
377992	410	4.145	3.800	6.000	9.000	1.1	16.6	15.3	14.1	-4.5	TBD	B, S	0.02	JG7708-4145-5	GM1004-039
377993	411	4.150	3.800	6.000	9.000	1.1	16.6	15.3	14.1	-4.5	TBD	B, S	0.025	JG7708-4145-5	GM1004-039
377994	412	4.155	3.800	6.000	9.000	1.1	16.6	15.4	14.2	-4.5	TBD	B, S	0.03	JG7708-4155-5	GM1004-039
377995	414	4.165	3.800	6.000	9.000	1.1	16.7	15.4	14.2	-4.5	TBD	B, S	0.04	JG7708-4165-5	GM1004-039
377996	401	4.125	3.750	6.000	9.000	1.125	16.2	15	13.9	-4.5	TBD	B, S	STD	JG7708-4125-5	GM1003-039
377997	402	4.130	3.750	6.000	9.000	1.125	16.2	15	13.9	-4.5	TBD	B, S	0.005	JG7708-4130-5	GM1003-039
377998	403	4.135	3.750	6.000	9.000	1.125	16.3	15	13.9	-4.5	TBD	B, S	0.01	JG7708-4135-5	GM1003-039
377999	404	4.140	3.750	6.000	9.000	1.125	16.3	15	13.9	-4.5	TBD	B, S	0.015	JG7708-4135-5	GM1004-039
378000	405	4.145	3.750	6.000	9.000	1.125	16.3	15	14	-4.5	TBD	B, S	0.02	JG7708-4145-5	GM1004-039
378001	406	4.150	3.750	6.000	9.000	1.125	16.4	15.1	14	-4.5	TBD	B, S	0.025	JG7708-4145-5	GM1004-039
378002	407	4.155	3.750	6.000	9.000	1.125	16.4	15.1	14	-4.5	TBD	B, S	0.03	JG7708-4155-5	GM1004-039
378003	409	4.165	3.750	6.000	9.000	1.125	16.5	15.2	14.1	-4.5	TBD	B, S	0.04	JG7708-4165-5	GM1004-039
378004	406	4.125	3.800	5.850	9.000	1.25	16.4	15.1	14	-4.5	371	S	STD	JG7708-4125-5	GM1003-039
378005	407	4.130	3.800	5.850	9.000	1.25	16.5	15.2	14	-4.5	373	S	0.005	JG7708-4130-5	GM1003-039
378006	408	4.135	3.800	5.850	9.000	1.25	16.5	15.2	14.1	-4.5	375	S	0.01	JG7708-4135-5	GM1003-039
378007	409	4.140	3.800	5.850	9.000	1.25	16.5	15.2	14.1	-4.5	376	S	0.015	JG7708-4135-5	GM1004-039
378008	410	4.145	3.800	5.850	9.000	1.25	16.6	15.3	14.1	-4.5	377	S	0.02	JG7708-4145-5	GM1004-039
378009	411	4.150	3.800	5.850	9.000	1.25	16.6	15.3	14.1	-4.5	378	S	0.025	JG7708-4145-5	GM1004-039
378010	412	4.155	3.800	5.850	9.000	1.25	16.6	15.4	14.2	-4.5	379	S	0.03	JG7708-4155-5	GM1004-039
378011	414	4.165	3.800	5.850	9.000	1.25	16.7	15.4	14.2	-4.5	380	S	0.04	JG7708-4165-5	GM1004-039

Valve pockets can be cut .025" deeper on part numbers 377980 - 378011